

Dreamtec+ (63000027)

Version: 27/03/2020

Product description

Underlay for click vinyl planks and tiles.

Logistic information

	contains	length	width	thickness	weight
1 box		8500 mm	1180 mm	1.5 mm	2.28 kg
1 pallet	27 boxes	2410 mm	800 mm	462 mm	61.52 kg

Installation

Folds out flat straight away , for floating installation.
Sliceable with a standard cutter knife.



Product composition

Pressure resistant foam non woven with antislip surface and integrated water vapour layer.

Storage

Do not store outdoors, protect from exposure to sunlight. Prevent electrostatic discharges, keep away from ignition source, do not smoke.

Requirements


Characteristics	Method	Value
Thickness of the underlay measured	EN 823	1.5 (+/- 15%) mm
Foam colour		Silver
Reflected walking sound	ISO 10140	≤ 3 dB
Impact sound reduction	ISO 10140	20 dB
Compressive strenght (at 0.5 mm deformation)	EN 826	CS > 400 kPa (-40 t/m ²)
Punctual conformability	ISO 868 / TS 16354	+/- 1 mm
Thermal resistance	DIN 4108	0.043 m ² K/W
Water absorption	EN 12087	< 1 %
Coefficient of friction	ISO 8295	> 0.8
Dynamic load resistance	EN 13793 / TS 16354	DL > 100000 cycles



impact sound
-20 dB



-62% walking
sound
reduction



suitable for
floor heating




corrects
unevenness &
protects loc
system



integrated
moisture
barrier



protects
against loads



Information sur le niveau d'émission de substances volatiles dans l'air intérieur
présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très
faibles émissions) à C (fortes émissions).