

08/2022

	contains	m <sup>2</sup>	ft <sup>2</sup>	weight
1 pack Chateau	24 planks	1,02 m <sup>2</sup>	10.94 ft <sup>2</sup>	7,3 kg
1 pallet Chateau	48 packs	48,77 m <sup>2</sup>	524.97 ft <sup>2</sup>	365 kg

## product specifications

Dimensions	504 x 84 mm
Total thickness	8 mm
Bevels	4
Loc System	Chateau Loc - type A and type B
Level of use according to European standard EN10874	23 heavy domestic use
	32 general commercial use
Residential warranty	lifetime
Commercial warranty	5 years

Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com).

## composition

Surface layer	Direct laminated paper, impregnated with melamine resin.
Substrate	Moisture resistant High Density Fiberboard (HDF).
Backing	Direct laminated paper, impregnated with melamine resin.

## test results

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	Small ball : ≥ 12 N - Big ball : ≥ 750 mm
Thickness swelling	EN13329	12% (requirement ≤ 18%)
Fire resistance	EN14041	Cfl-S1
Formaldehyde emission	EN14041	E1
Slip resistance	EN14041	DS
Density	EN323	900 kg/m <sup>3</sup>
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN424	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage
Thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m <sup>2</sup> K/W – Suitable for floor heating/cooling. Detailed instructions on <a href="http://www.berryalloc.com">www.berryalloc.com</a>

## certificates/labels

- DOP : 170-DPLA18-1  
UKCA : 170-DPLA22-1
- Sustainability of forests :  
PEFC certified (07-31-229)
- Labelling according to French  
VOC emission regulation: A

