



### PRODUCT DESCRIPTION

Dimensions	1288mm x 190mm
Thickness	8mm
Bevels	-
Loc System	DuoLoc
Classification of use	Class 23/32 According to European Standard EN13329

	Contains	m <sup>2</sup>	ft <sup>2</sup>	Weight
1 pack	9 planks	2,20 m <sup>2</sup>	23,71 ft <sup>2</sup>	15,7 kg
1 pallet	56 packs	123,34 m <sup>2</sup>	1327,61 ft <sup>2</sup>	891 kg

### COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF)
Backing	Direct laminated paper, impregnated with melamine resin

### TESTED VALUE

Abrasion resistance

Impact resistance

Thickness swelling

Fire resistance

Formaldehyde

Slipperiness

Density

Resistance to staining

Resistance to cigarette burns

Effect of a furniture leg

Effect of a castor chair

Thermal resistance in combination with underlay Excellence Plus

### METHOD

EN13329

EN13329

EN13329

EN14041

EN14041

EN14041

EN323

EN438

EN438

EN424

EN425

### TEST RESULTS

AC4 (IP≥4000)

Small ball : ≥ 12 N - Big ball : ≥ 750 mm

12% (requirement ≤ 18%)

Cfl-S1

E1

DS

900 kg

5 (groups 1+2); 4 (group 3)

4

No damage (foot type 0)

No change in appearance or damage

0,08 m<sup>2</sup>K/W – Suitable for floor heating/cooling.  
Detailed instructions on [www.berryalloc.com](http://www.berryalloc.com)

### CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- DOP : 170-DPLA18-1

### WARRANTY

- Lifetime Residential Warranty
- 5 Years of Commercial Warranty
- Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

